



Magna™ SW WT Range

Machine Tool Slide Lubricants

Description

Castrol Magna SW WT Range (previously called Magna™ BDX 68 + CFX 220) slideway oils are based upon highly refined mineral oils, which incorporate tackiness and lubricity additives.

Application

Magna SW WT Range slideway oils give smooth slideway movement under heavy loads.

They are high performance emulsifying slideway lubricants specially formulated for use in individual machines where coolant and oil separation is not practical.

Both Magna SW 68 WT and SW 220 WT will emulsify with the metalworking fluid in use, however, this may cause instability of the coolant over a period of time.

Advantages

- Incorporate tackiness and lubricity additives
- Exceptionally low frictional forces and good "stick-slip" resistance
- Good protection against metal corrosion and staining
- Suitable for all types of slideway materials

Typical Characteristics

Name	Method	Units	SW 68 WT	SW 220 WT
Density @ 20°C / 68°F	ASTM D4052 / ISO 12185	kg/m ³	880	884
Kinematic Viscosity @ 40°C / 104°F	ASTM D445 / ISO 3104	-	68	220
Kinematic Viscosity @ 100°C / 212°F	ASTM D445 / ISO 3104	mm ² /s	8.73	19.6
Viscosity Index	ASTM D2270 / ISO 2909	mm ² /s	100	100
Flash Point - closed cup method	ASTM D93 / ISO 2719	°C/°F	243 / 453	243 /470
Pour Point	ASTM D97 / ISO 3016	°C/°F	-12/+10	-12/+10
Copper corrosion (3 hrs@100°C/212°F)	ASTM D130 / ISO 2160	Rating	Pass	Pass
Rust test - distilled water (24 hrs)	ASTM D665A / ISO 7120	-	1	1

Subject to usual manufacturing tolerances.

This product was previously called Magna BDX 68 + CFX 220. The name was changed in 2015.

Magna™ SW WT Range

19 May 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial , North America Inc. , 150 West Warrenville Road , 603 1E Naperville , IL 60563
Tel: (877) 641 1600 Fax: (877) 648 9801
www.castrol.com/industrial