



Lusin® Protect G 31 F

Wax-Based Anti-Corrosion and Lubricating Agent

Benefits

- Food grade lubricant, NSF H1 registered
- Long-lasting protection against corrosion
- Stable whitish film resistant to handling
- Easy to remove

Description

Lusin® Protect G 31 F is a highly efficient anti-corrosion agent that also shows lubricating properties. The delayed generation of the solid protective film enables Lusin® Protect G 31 F to penetrate into very fine cracks. Lusin® Protect G 31 F conforms to H1 category code and therefore complies with FDA 21 CFR §178.3570.

Typical Properties

Flash point	< -10 °C (14 °F)
Neutral Salt Spray Test according to DIN EN ISO 9227	No corrosion after 150 h

Application

Lusin® Protect G 31 F is mainly used to protect moulds and dies dedicated for processing thermoplastic resins against corrosion.

Lusin® Protect G 31 F only shows maximum anti-corrosion properties when applied on dry and clean metal surfaces. For cleaning it is recommended to use Lusin® Clean L 23 F as a mould cleaning agent and Lusin® Clean L 52 F as a degreasing agent. Both products are NSF registered.

Optimal film generation is only ensured if Lusin® Protect G 31 F is applied in several thin layers, taking particular care to cover edges and undercuts.

Lusin® Protect G 31 F can either be removed by producing parts, thus transferring the protective agent to the produced parts or by the use of the cleaning agent Lusin® Clean L 52 F.

In terms of subsequent treatment of the produced parts, such as lacquering, printing or gluing, preliminary tests are recommended.

Storage / Handling

Lusin® Protect G 31 F should be stored in a dry indoor area at room temperature. For further information on hazards etc. please refer to safety data sheet.

Shelf life

24 months

Packaging

Aerosol: 400 mL with 12 cans per box

Further Information

Request information on our complete range of materials for this industry.

Legal Notice

The technical information and suggestions for use contained herein is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a professional with technical experience. It does not release the customer from the obligation of performing own tests with the product selected for a specific application. While the information and suggestions are believed to be accurate and reliable, nothing stated in this bulletin is to be taken as a warranty either expressed or implied.