



Cartucce a soffietto compatibili



UTILIZZABILI SU MACCHINE:

MAZAK
DOOSAN (Macchina Utensile)
SUMITOMO (Presse Plastica)
FANUC (Presse Plastica)

Sistemi compatibili
LUBE P207
HALS HGP -10LMC

Alternativo ai grassi

LHL X-100 / 700 (LUBE)
KLUEBER S 88 PLUS (HALS)
MYS 7 (LUBE/SUMITOMO)

Prodotto:
TURMOGREASE NM 00
Olio base: Minerale 150 cSt
Addensante: Poliurea
Consistenza NLGI 00

Disponibilità: 15 Maggio 2022



TURMOGREASE NM 00

G P 00 N -30



Date of issue: 24.10.2018

TURMOGREASE NM 00 is a multipurpose grease for manifold applications in the temperature range of -30°C to + 140°C. Because of its excellent pumpability also at low temperatures it can be used especially for central lubrication systems.

Special properties

- Resistant to cold/hot water
- High load carrying capacity
- Excellent wear protection
- Very good corrosion protection
- Conveyable in central-lubrication systems

| Product Characteristics | Value | Dimension | Norm / Standard |
|---|-------------|--------------------|-----------------|
| Colour | beige | | |
| Density at 20°C | 0,90 | g/cm ³ | DIN 51757 |
| Operating temperature range | -30 to 140 | °C | |
| Thickener | Polyurea | | |
| Base oil | Mineral oil | | |
| Kin. viscosity of the base oil at 40°C | 155 | mm ² /s | DIN EN ISO 3104 |
| Kin. viscosity of the base oil at 100°C | 14,9 | mm ² /s | DIN EN ISO 3104 |
| Worked penetration | 400 – 430 | mm/10 | DIN ISO 2137 |
| Consistency class (NLGI) | 00 | | DIN 51818 |
| Dropping point | > 230 | °C | DIN ISO 2176 |
| Resistance to water | 0 – 90 | | DIN 51807 |
| Corrosion protection (SKF-Emcor) | 0 / 0 | | DIN 51802 |

Application

TURMOGREASE NM 00 is used for gears and sliding bearings in industrial plants and in the automotive industry.

Gears and sliding bearings in machine construction (f. ex. calanders, mixers), in the automotive industry, in wet working machines, as well as pumps, washing and rinsing bearings.

Packaging units

20 x 400 g cartridges, 6 x 1 kg cans, 5 kg bucket, 25 kg hobbock, 50 kg hobbock, 180 kg drum

