



# TURMOPLEX EL 000 EP

G P 000 K -30



Date of issue: 29.06.2023

**TURMOPLEX EL 000 EP** is a soft semi-fluid gear grease with lithium thickener and excellent lubrication properties, also under wet and dusty operating conditions.

## Special properties

- High oxidation resistance
- High load carrying capacity
- Very good corrosion protection
- Conveyable in central-lubrication systems
- Very good wear protection
- Usable in feeding lubricating systems

Product Characteristics	Value	Dimension	Norm / Standard
Colour	green, brownish		
Density at 20°C	0,89	g/cm <sup>3</sup>	DIN EN ISO 2811-1
Operating temperature range	-35 to 120	°C	
Thickener	Lithium soap		
Base oil	Mineral oil		
Kin. viscosity of the base oil at 40°C	150	mm <sup>2</sup> /s	DIN EN ISO 3104
Kin. viscosity of the base oil at 100°C	14	mm <sup>2</sup> /s	DIN EN ISO 3104
Worked penetration	445 – 475	mm/10	DIN ISO 2137
Consistency class (NLGI)	000		DIN 51818
Dropping point	> 120	°C	DIN ISO 2176
Corrosion protection (SKF-Emcor)	0 / 0		DIN 51802
Four-ball test O.K. load / welded load	3400 / 3600	N	DIN 51350

## Application

Highly loaded gears and tooth clutches.

Recommended for central lubrication systems of trucks and gears at agricultural machinery and printing machines.

## Packaging units

6 x 1 kg can, 5 kg bucket, 25 kg hobbock, 50 kg hobbock, 180 kg drum



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: [webmaster@lubcon.com](mailto:webmaster@lubcon.com) · Internet: <http://www.lubcon.com>