



TURMOTEXOIL LP 22 W



Member of the FUCHS Group

Date of issue: 26.02.2025

TURMOTEXOIL LP 22 W is a special oil for the lubrication of knitting machines, based on white oil.

TURMOTEXOIL LP 22 W keeps the needles clean, extend service-life of needles and sinkers.

Special properties

- Good viscosity-temperature behaviour
- Low volatility
- High oxidation resistance (no resifinication)
- Very good wetting properties and high lubricity
- Very good wear protection
- Good vibration and noise damping
- Reduces operating temperatures
- Very easy to emulsify
- Washes out very well

Product Characteristics	Value	Dimension	Norm / Standard
Colour	transparent		
Density at 20°C	0,87	g/cm ³	DIN 51757
Oil type	White oil		
Kinematic viscosity at 40°C	22,2	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	4,4	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	108		DIN ISO 2909
Pour point	approx. -10	°C	DIN EN ISO 3016
Flash point	> 180	°C	DIN EN ISO 2592

Application

Needles, sinkers as well as needle and sinker cylinders.

Exact dosage by means of central lubrication systems.

Packaging units

5 l canister, 20 l canister, 60 l drum, 200 l drum, 1000 l container

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)

Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>