

## DISTACCANTE SINTETICO

DISTACCANTE SENZA SILICONE  
PER STAMPAGGIO DI MATERIE PLASTICHE

### CARATTERISTICHE

Aspetto:	Liquido trasparente
Base:	Miscela di polimeri e distaccanti a base sintetica.
Propellente:	Idrocarburi denaturati inodori.
Resistenza alle temperature:	-40°C/ +300°C
NON CONTIENE SILICONE	
CFC FREE	

### CAMPI D'IMPIEGO

Stampaggio materie plastiche.

### DESCRIZIONE

Pur essendo un ottimo antiadesivo e distaccante alla pari dei migliori prodotti siliconici, non presenta gli stessi inconvenienti, permettendo le seguenti operazioni: verniciatura, stampa, metallizzazione, cromatura, incollatura delle superfici interessate.

S'impiega quindi nei casi in cui le superfici dei materiali stampati debbano essere poi trattate e nei casi in cui l'aerosol possa dare inconvenienti nei comunicanti reparti di verniciatura o smaltatura.

Non intacca le superfici su cui è spruzzato.

### ISTRUZIONI D'IMPIEGO

STAMPAGGIO MATERIE PLASTICHE: pulire e sgrassare con cura le superfici degli stampi e spruzzarle a brevi getti da una distanza di circa 30 cm.

Per eliminare i residui si consiglia di usare un solvente.

### CONFEZIONI

Bombola Aerosol 400 ml

Cartoni da 25 pezzi

Codice 10610/04D

Data ultima revisione 25.11.2016

The information and recommendations contained in this document is offered in good faith based on our current knowledge and belief accurate at the date of publication. Nothing herein is to be considered as a warranty, express or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular purpose with local legislation and for obtaining the necessary certifications and authorisations. Siliconi Commerciale's sole warranty is that the products will meet its sales specification. The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.

® indicates a Registered TradeMarks of Siliconi Commerciale. All Rights Reserved.

SILICONI COMMERCIALE® Technical data- sheet

